# esigns Resin

Data Sheet Rev. #: 6

## AXIS™ M-120

#### MEDICAL GRADE EPOXY ADHESIVE

**APRIL 2017** 

#### **TECHNICAL DATA Product Description**

Axis M-120 is a high viscosity resin system designed for industrial adhesive applications. This two part epoxy is easily mixed, cures at room temperature and provides high peel resistance and shear strengths. Once cured it is resistant to an extensive range of chemicals and is stable over a wide temperature range.

#### APPLICATIONS

Industrial adhesive

#### **FEATURES**

- Medical Potting
- RoHS & REACH Compliant
  - Impact and peel resistant
  - Thermal shock resistant
  - Moisture resistant
  - Room temp cure

  - Long work life

### **SUBSTRATES**

 Ceramics • Plastics

#### PACKAGING

Dual Cartridges

TYPICAL PROPERTIES OF UNCURED MATERIAL		
Property	Value, Part A	Value, Part B
Chemical Class	Ероху	Amine
Appearance	Off White	Amber
Viscosity, 10 RPM 25°C, cps	-	112,000
Viscosity, 100 RPM 25°C, cps	3,200	-
Specific Gravity	1.16	1.00
Mix Ratio by Volume	2	1

TYPICAL PROPERTIES OF CURED MATERIAL		
Property	Value	
Lap Shear Strength, Al/Al, PSI	4,800	
Hardness, Shore	D80	
Ultimate Tensile Strength, PSI	5,900	
Elongation at Break, %	40	
Dielectric Strength, PSI	25	
Operating Temperature (°C)	-60 to 150	
Volume Resistivity, Ω-cm	-	

\*All properties given are typical values and are not intended for use in preparing specifications.

CURE OVERVIEW		
Pot Life @ 25°C, Min	120	
Cure Options: Hr @ 25°C	48	
Cure Options: Hr @ 65°C	2	
Clean-Up Solvent	Isopropyl Alcohol	

#### SHELF LIFE, STORAGE

18 ± 10°C Bulk: 1 Year DOM; Packaged: 6 Months DOM

MATERIAL IS LIGHT SENSITIVE. CONSULT SDS FOR SAFE HANDLING RECOMMENDATIONS.

#### THIS MATERIAL IS SOLD FOR INDUSTRIAL USE ONLY

**RESIN DESIGNS MAKES NO EXPRESS OR IMPLIED REPRESENTATIONS OR WARRANTIES, INCLUDING** WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE, WITH RESPECT TO THIS PRODUCT AND GUARANTEES NO PARTICULAR OUTCOME OR RESULT FROM ITS USE. RESIN DESIGNS' LIABILITY TO CUSTOMER WITH RESPECT TO THIS PRODUCT SHALL IN NO EVENT EXCEED THE AMOUNT PAID BY CUSTOMER FOR IT.